Windshield Washer Solvent

SECTION I - IDENTIFICATION



Rite-Kem, Inc.

645 Westmoreland Drive

Tupelo, MS 38801 (662) 840-6060

Chemtrec :..... (800) 424-9300

Product Number WIND-WASH

Product Name Windshield Washer Solvent **Synonyms** NSN 6850-01-368-4799

 CAS Number
 67-56-1

 Date Prepared
 5/28/2015

 Revision Number
 4/19/2018

Recommended Use Industrial Use Only

SECTION II - HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Classification

Flammable Liquids

Acute Toxicity, Oral

Acute Toxicity, Dermal

Acute Toxicity, Inhalation

Category 3

Acute Toxicity, Inhalation

Category 3

Specific target organ toxicity, single exposure

Category 1

DANGER!

GHS LABEL:







Hazard Statements

H225 Highly flammable liquid and vapor

H301 Toxic if swallowed

H311 Toxic in contact with skin

H331 Toxic if inhaled

H370 Causes damage to organs

Windshield Washer Solvent

Precautionary Statements

P210	Keep away from heat, hot surfaces, sparks,open flames, and other ignition, sources. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/light]/ equipment, etc.
P242	Use only non-sparking tools.
P243	Take precautionary measures to prevent static discharge.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated are.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352	IF ON SKIN: Wash with plenty of water/
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+340	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
P308+311	IF exposed or concerned: Call POISON CENTER/doctor/physician
P311	Call a POISON CENTER or a doctor/physician.
P312	Call a POISON CENTER or a doctor/physician if you feel unwell.
P321	Specific treatment (see on this label).
P330	Rinse mouth.
P362+364	Take off immediatley all contaminated clothing and wash it before reuse.
P370+378	In case of fire: Use to extinguish.
P403+233	Store in a well ventilated place. Keep container tightly closed.
P403+235	Store in a well ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to

Windshield Washer Solvent

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS#	Component%	OSHA PEL	ACGIH TLV
Methanol	67-56-1		200 ppm(Skin)	200 ppm(Skin)

SECTION IV - FIRST AID MEASURES

Contact with eyes: Flush with water for 15 minutes. Seek immediate medical attention.

Skin contact: Wash exposed areas with water and mild soap. Remove contaminated clothing

immediatelyand launder before reuse. If irritations persist, seek immediate medical

attention.

Inhalation: Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is

affected or stopped. Seek immediate medical attention.

Ingestion: Give large quantities of water . Never give anything by mouth to an unconsciuous

person.

SECTION V - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, CO2, dry chemical.

Special Fire Fighting Procedures Use self-contained breathing apparatus and full bunker gear in fire areas.

Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water

used for cooling.

Unusual Fire Fighting Hazards: Product is flammable and may be ignited by heat, sparks, flames or other

sources of ignition (e.g., static electricity, pilot lights or mechanical/electrical equipment). Vapors are heavier than air and may accumulate in low areas. Vapors may travel considerable distances to a source of ignition where they can ignite, flashback or explode. May create vapor/air explosion hazard indoors, outdoors or in sewers. If container is not properly cooled, it can

explode in the heat of a fire.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep all sources of ignition and hot metal surfaces away from spill or

release.

Evacuate all unprotected personnel from the area.

Environmental Precautions: Prevent liquid from entering drains, sewers or waterways.

Notify proper authorities. Reportable Quantity is 5,000 pounds or 758

gallons.

Contain spill if it can be done with minimal risk.

Windshield Washer Solvent

Methods for Cleaning Up: Use foam on spills to minimize vapors.

Using only non-sparking tools and explosion proof equipment, collect

spill on absorbent material and put into approved container.

SECTION VII - HANDLING AND STORAGE

Handling and Storage:

- NFPA Class I storage.
- Vent container carefully before opening.
- Bond and ground all equipment when transferring from one vessel to another. The use of ecplosion-proof equipment is recommended.
- "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
- Keep containers tightly closed when not in use.
- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

Component Name	CAS#	OSHA PEL	ACGIH TLV
Methanol	67-56-1	200 ppm(Skin)	200 ppm(Skin)

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or

TLV.

Monitoring: Follow accepted work practices for handling a flammable material.

Do not eat, drink or smoke in areas where this chemical is uised or stored.

Have eye wash stations and safety showers readily available.

Personal Protective Equipment (PPE)

Eye Protection: Goggles or approved OSHA device with side shields; do not wear contact

lenses when handling this product.

Skin Protection: Impervious solvent resistent gloves.

Impervious apron and work boots recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is

unknownor above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Windshield Washer Solvent

Appearance	Clear, Bluish Green Liquid
Odor	Strong Characteristic Alcohol Odor
pH@25°C	-
Melting/Freezing Point	-
Flashpoint	54°F (11°C); TCC
Specific Gravity	0.7793
Soluability	Complete
Auto-Ignition Temperature	-
Decomposition Temperature	-
VOC Content	69% (4.56#/gal)
Odor Threshold	-
Boiling Range	148°F
Evaporation Point	2.0 (Butyl Acetate=1)
Flammable Limits - Upper	36.5%
Flammable Limits - Lower	5.5%
Vapor Pressure	96 mmHg @ 20°C
Vapor Density (Air=1)	1.11 (Air=1)
Viscosity	-

SECTION X - STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Extreme heat and ignition sources.

Hazardous Decomposition/Byproducts: CO, CO2, and noxious smoke under extreme fire conditions

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

Incompatibilities: Strong acids and bases, strong oxidizers

Windshield Washer Solvent

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure: Contact and inhalation; ingestion possible.

Inhalation: Low to moderate degree of toxicity by inhalation.

May cause respiratory tract irritation. Inhalation of vapors may cause

drowsiness and dizziness.

Eye Contact: Causes eye irritation including stinging, watering and redness which

may result in corneal injury.

Skin Contact: Contact may cause mild sking irritation including redness, burning and

drying/cracking of the skin.

Repeated or prolonged contact with large amounts of this material may

result in absorption through the skin to produce toxic effects.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting

and cause chemical pneumonia and edema.

Moderate to high degee of toxicity by ingestion. May be harmful or

fatal if swallowed.

Acute Toxicity Value: See Health Hazards below.

Chronic (Long Term) Effects: See Health Hazards above.

Toxicity:

Component Name	LD50	LC50
Methanol	G. G.	Inhalation - rat - 4 h - 128.2 mg/l;
	rat - 1,187 - 2,769 mg/kg;	Inhalation - rat - 6 h - 87.6 mg/l

Reproductive Effects Not Applicable

Teratogenicity Not Applicable

Mutagenicity Not Applicable

Embryotoxicity Not Applicable

Sensitization to Product Not Applicable

Synergistic Products Not Applicable

Carcinogenicity Not Listed as a Carcinogen

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Information not available.

Windshield Washer Solvent

Mobility: Information not available.

Degradability: Information not available.

BioAccumulation: Information not available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow Federal, state, and local regulations.

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: UN1230, Methanol, 3, PG-II

Contains: Methanol

Hazard Class and Label: 3

Identification Number: UN 1230

Packaging Group:

Other Shipping Info:

IMDG: METHANOL, UN1230,3(6.1), PG II

IATA: METHANOL, UN1230,3(6.1), PG II

SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X	X	X		

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

Component Name	CAS#	% by wt.
Methanol	67-56-1	70

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

Windshield Washer Solvent

Component Name	CAS#	% by wt.	RQ (lbs.)
Methanol	67-56-1	70	5,000

CALIFORNIA PROPOSITION 65:

This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

SECTION XVI - OTHER INFORMATION

Additional: Other Information (XVI) - Additional Information #1

Specification Information

Department issuing data sheet: Quality Control

Email address: customerservice@ritekem.com

Training necessary: Follow product use instructions listed on the label. Any additional

questions, contact Customer Service at 662-840-6060 or email

customerservice@ritekem.com.

Disclaimer:

The information in this Safety Data Sheet and product label is believed to be accurate and reliable as of the date issued. Rite-Kem makes no warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. Accordingly, Rite-Kem will not be responsible for damages resulting from use of or reliance upon this information. The user is responsible for determining whether the Rite-Kem product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application on a Rite-Kem product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Rite-Kem product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.