

Safety Data Sheet

Snow Slide

SECTION I - IDENTIFICATION

	Rite-Kem, Inc. 645 Westmoreland Drive Tupelo, MS 38801 (662) 840-6060 Chemtrec :..... (800) 424-9300
---	--

Product Number Snow Slide
Product Name Snow Slide
Synonyms
CAS Number 64742-47-8
Date Prepared 5/28/2015
Revision Number 4/19/2018
Recommended Use Industrial Use Only

SECTION II - HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Classification

Aspiration Hazard	Category 1
Skin Corrosion/Irritation	Category 2
Specific target organ toxicity, single exposure, N	Category 3
Hazardous to the aquatic environment, long-term hazard	Category 2

DANGER!

GHS LABEL:



Hazard Statements

H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause dizziness or drowsiness
H411	Toxic to aquatic life with long lasting effects

Safety Data Sheet

Snow Slide

Precautionary Statements

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated are.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+352	IF ON SKIN: Wash with plenty of water/...
P304+340	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER or a doctor/physician if you feel unwell.
P321	Specific treatment (see ... on this label).
P331	Do NOT induce vomiting.
P332+313	If skin irritation occurs: get medical advice/attention.
P362+364	Take off immediatley all contaminated clothing and wash it before reuse.
P391	Collect spillage.
P403+233	Store in a well ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to...

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS #	Component%	OSHA PEL	ACGIH TLV
Petroleum Distillates, Hydrotreated, Light	64742-47-8		500 ppm	500 ppm

SECTION IV - FIRST AID MEASURES

Contact with eyes: Flush with water for 15 minutes. Seek immediate medical attention.

Skin contact: Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, seek immediate medical attention.

Inhalation: Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is affected or stopped. Seek immediate medical attention.

Safety Data Sheet

Snow Slide

Ingestion: If swallowed. Do not induce vomiting. Seek immediate medical attention.

SECTION V - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, CO₂, dry chemical.

Special Fire Fighting Procedures Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

Unusual Fire Fighting Hazards: Product is flammable and may be ignited by heat, sparks, flames or other sources of ignition (e.g., static electricity, pilot lights or mechanical/electrical equipment). Vapors are heavier than air and may accumulate in low areas. Vapors may travel considerable distance to a source of ignition where they can ignite, flashback or explode. May create vapor/air explosion hazard indoors, outdoors or in sewers. If container is not properly cooled, it can explode in the heat of a fire.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep all sources of ignition and hot metal surfaces away from spill or release.

Evacuate all unprotected personnel from the area.

Environmental Precautions: Prevent liquid from entering drains, sewers or waterways.

Contain spill if it can be done with minimal risk.

Notify proper authorities.

Methods for Cleaning Up: Use foam on spills to minimize vapors.

Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container.

SECTION VII - HANDLING AND STORAGE

- Handling and Storage:**
- Vent container carefully before opening.
 - Bond and ground all equipment when transferring from one vessel to another. The use of explosion-proof equipment is recommended.
 - "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
 - Keep containers tightly closed when not in use.
 - Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.
 - NFPA Class III A storage.

Safety Data Sheet

Snow Slide

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

Component Name	CAS #	OSHA PEL	ACGIH TLV
Petroleum Distillates, Hydrotreated, Light	64742-47-8	500 ppm	500 ppm

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

Monitoring: Follow accepted work practices for handling a flammable material.
Do not eat, drink or smoke in areas where this chemical is used or stored.
Have eye wash stations and safety showers readily available.

Personal Protective Equipment (PPE)

Eye Protection: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

Skin Protection: Impervious solvent resistant gloves.
Impervious apron and work boots recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, Colorless Liquid
Odor	Mild Odor
pH@25°C	-
Melting/Freezing Point	N/A
Flashpoint	>145 F (TCC)
Specific Gravity	0.79
Solubility	Negligible
Auto-Ignition Temperature	-
Decomposition Temperature	-
VOC Content	100% (6.6#/gal)
Odor Threshold	-
Boiling Range	>370°F
Evaporation Point	<1 Where Ether=1
Flammable Limits - Upper	6.0%
Flammable Limits - Lower	1.0%
Vapor Pressure	<0.5 mmHg @ 100°F
Vapor Density (Air=1)	6.2 (Air=1)
Viscosity	-

SECTION X - STABILITY AND REACTIVITY

Stability: Stable

Safety Data Sheet

Snow Slide

Conditions to Avoid: Extreme heat and ignition sources.

Hazardous Decomposition/Byproducts: CO and CO₂

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

Incompatibilities: Strong oxidizers

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure: Contact and inhalation; ingestion possible.

Inhalation: May cause irritation to the upper respiratory tract and CNS depression. Low to moderate degree of toxicity by inhalation.

Eye Contact: Causes eye irritation including stinging, watering and redness which may result in corneal injury.

Skin Contact: Contact may cause mild skin irritation including redness, burning and drying/cracking of the skin.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia and edema.

Acute Toxicity Value: See Health Hazards below.

Chronic (Long Term) Effects: See Health Hazards above.

Toxicity:

Component Name	LD50	LC50
Petroleum Distillates, Hydrotreated, Light	Oral - rat - > 5000 mg/kg - Dermal - rabbit - >2000mg/kg	Inhalation - rat - >5 mg/l / 4 h

Reproductive Effects Not Applicable

Teratogenicity Not Applicable

Mutagenicity Not Applicable

Embryotoxicity Not Applicable

Safety Data Sheet

Snow Slide

Sensitization to Product Not Applicable

Synergistic Products Not Applicable

Carcinogenicity Not Listed as a Carcinogen

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Information not available.

Mobility: Information not available.

Degradability: Information not available.

BioAccumulation: Information not available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow Federal, state, and local regulations.

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: Combustible Liquid, N.O.S.

Contains: Petroleum Distillates

Hazard Class and Label:

Identification Number: NA 1993

Packaging Group: III

Other Shipping Info:

SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Safety Data Sheet

Snow Slide

Acute	Chronic	Fire	Pressure	Reactive
X	X	X		

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

No chemicals in this material are subject to the reporting requirements.

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

CALIFORNIA PROPOSITION 65:

No chemicals in this material are subject to the reporting requirements.

SECTION XVI - OTHER INFORMATION

HMIS Health: 1

HMIS Flammability: 2

HMIS Reactivity: 0

Additional:

Specification Information

Department issuing data sheet: Quality Control

Email address: customerservice@ritekem.com

Training necessary: Follow product use instructions listed on the label. Any additional questions, contact Customer Service at 662-840-6060 or email customerservice@ritekem.com.

Disclaimer:

The information in this Safety Data Sheet and product label is believed to be accurate and reliable as of the date issued. Rite-Kem makes no warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. Accordingly, Rite-Kem will not be responsible for damages resulting from use of or reliance upon this information. The user is responsible for determining whether the Rite-Kem product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application on a Rite-Kem product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Rite-Kem product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

