Coil Kleen O

# **SECTION I - IDENTIFICATION**



Rite-Kem, Inc.

645 Westmoreland Drive

Tupelo, MS 38801 (662) 840-6060

Chemtrec :..... (800) 424-9300

Product Number COIL-KL-O
Product Name Coil Kleen O

**Synonyms** 

CAS Number Multiple
Date Prepared 5/28/2015
Revision Number 4/19/2018

Recommended Use Industrial Use Only

# **SECTION II - HAZARDOUS IDENTIFICATION**

# **GHS CLASSIFICATION:**

## Classification

Corrosive to Metals Category 1

Skin Corrosion/Irritation Category 1A, B, C

Serious Eye Damage/Eye Irritation Category 1
Specific target organ toxicity, single exposure Category 1

### DANGER!

# **GHS LABEL:**





## **Hazard Statements**

H290 May be corrosive to metals

H314 Causes severe burns and eye damage

H318 Causes serious eye damage H370 Causes damage to organs

#### Coil Kleen O

## **Precautionary Statements**

P234

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+340	IF INHALED: Remove victim to fresh air and keep comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and

easy to do so - continue rinsing.

Keep only in original packaging

P308+311 IF exposed or concerned: Call POISON CENTER/doctor/physician

P310 Immediately call a POISON CENTER or doctor/physician.

P321 Specific treatment (see ... on this label).

Wash contaminated clothing before reuse. P363

p390 Absorb spillage to prevent material damage.

P405 Store locked up.

P406 Store in a corrosive resistant/... container with a resistant inner liner.

P501 Dispose of contents/container to...

### **SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS**

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS#	Component%	OSHA PEL	ACGIH TLV
Hydrogen fluoride	7664-39-3		3.0 ppm	0.5 ppm
Sulfuric Acid	7664-93-9		1 mg/m³ (Ceiling)	1 mg/m³ (Ceiling)

### **SECTION IV - FIRST AID MEASURES**

Contact with eyes: Flush with water for 15 minutes. Seek immediate medical attention.

Skin contact: Wash exposed areas with water and mild soap. Remove contaminated clothing

immediatelyand launder before reuse. If irritations persist, seek immediate medical

attention.

Coil Kleen O

**Inhalation:** Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is

affected or stopped. Seek immediate medical attention.

**Ingestion:** If swallowed. Do not induce vomiting. Seek immediate medical attetntion.

#### **SECTION V - FIREFIGHTING MEASURES**

Suitable Extinguishing Media: Water fog, foam, CO2, dry chemical.

**Special Fire Fighting Procedures** Use self-contained breathing apparatus and full bunker gear in fire areas.

Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water

used for cooling.

**Unusual Fire Fighting Hazards:** Contact with reactive metals can generate hydrogen gas, which is flamable.

#### **SECTION VI - ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:** Evacuate all unprotected personnel from the area.

Environmental Precautions: Contain spill if it can be done with minimal risk. Prevent liquid from

entering drains, sewers or waterways. Notify proper authorities.

**Methods for Cleaning Up:** Cover with sodium bicarbonate or a soda ash/slaked lime minture

(50/50). Mix and add water if necessary to form a slurry and complete neatralization. Scoop up slurry and wash site with soda ash solution.

#### **SECTION VII - HANDLING AND STORAGE**

**Handling and Storage:** • Keep containers tightly closed when not in use.

• If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required

ventilation or exhaust systems may be required.

### SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

#### **EXPOSURE LIMITS:**

Component Name	CAS#	OSHA PEL	ACGIH TLV
Hydrogen fluoride	7664-39-3	3.0 ppm	0.5 ppm
Sulfuric Acid	7664-93-9	1 mg/m³ (Ceiling)	1 mg/m³ (Ceiling)

**Engineering Controls:** Adequate local or mechanical to reduce vapor or mist to below the PEL or

TLV.

Coil Kleen O

**Monitoring:** Follow accepted work practices for handling a corrosive material.

**Personal Protective Equipment (PPE)** 

**Eye Protection:** Goggles or approved OSHA device with side shields; do not wear contact

lenses when handling this product.

**Skin Protection:** Impervious solvent resistent gloves. Impervious apron and work boots

recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is

unknownor above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES			
Appearance	Colorless Liquid		
Odor	Strong Pungent		
pH@25°C	1.08		
Melting/Freezing Point	No Data Available		
Flashpoint	No Data Available		
Specific Gravity	1.1885		
Soluability	Soluable		
Auto-Ignition Temperature	No Data Available		
<b>Decomposition Temperature</b>	No Data Available		
VOC Content	No Data Available		
Odor Threshold			
Boiling Range	No Data Available		
Evaporation Point	2.0 (Butyl Acetate = 1)		
Flammable Limits - Upper	No Data Available		
Flammable Limits - Lower	No Data Available		
Vapor Pressure	160 mmHg @ 20°C		
Vapor Density (Air=1)	1.267		
Viscosity	No Data Available		

### SECTION X - STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Material is very corrosive and will attack most metals and

evolve hydrogen gas.

Hazardous Decomposition/Byproducts: Reaction with reactive metals may produce flammable

hydrogen; reaction with bases can be violent and produces

extreme heat.

Hazardous Polymerization: Will not occur.

Coil Kleen O

Polymerization Conditions to Avoid: None

**Incompatibilities:** Strong Oxidizers and bases

Metals

### **SECTION XI - TOXICOLOGICAL INFORMATION**

**Likely Route of Exposure:** Contact and inhalation; ingestion possible.

**Inhalation:** Can cause damage to nasal and respiratory passages.

**Eye Contact:** Will cause severe burns on contact and will damage the eyes.

**Skin Contact:** Causes burns, possible deep ulceration.

**Ingestion:** Causes severe damage to mucous membranes and deep tissues, a

result in death on penetration to vital areas.

**Toxicity:** 

Component Name	LD50	LC50
Hydrogen fluoride	Not Established	Not Established
Sulfuric Acid	Oral - rat - 2140 mg/kg	Inhalation - mouse - 320 mg/m3/2H; Inhalation - rat - 51-

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Applicable	Not Applicable	Not Applicable	Not Applicable		Not Applicable

### **SECTION XII - ECOLOGICAL INFORMATION**

**Ecotoxicity:** Information not available.

**Mobility:** Information not available.

**Degradability:** Information not available.

BioAccumulation: Information not available.

Coil Kleen O

### **SECTION XIII - WASTE DISPOSAL CONSIDERATIONS**

Follow Federal, state, and local regulations.

### **SECTION XIV - TRANSPORT INFORMATION**

#### **DOT SHIPPING INFORMATION**

Proper Shipping Name: Corrosive Liquid
Contains: Hydroflouric Acid

Hazard Class and Label: 8

**Identification Number:** UN1760

Packaging Group:

Other Shipping Info:

#### **SECTION XV - REGULATORY INFORMATION**

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

## SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

Component Name	CAS#	% by wt.	RQ (lbs.)	TPQ (lbs.)
Hydrogen fluoride	7664-39-3			100
Sulfuric Acid	7664-93-9			1,000

### SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X	X			X

## **SARA TITLE III SECTION 313 SUPPLIER INFORMATION:**

Component Name	CAS#	% by wt.
Hydrogen fluoride	7664-39-3	

## **CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:**

Component Name	CAS#	% by wt.	RQ (lbs.)
Hydrogen fluoride	7664-39-3		100
Sulfuric Acid	7664-93-9		1,000

# **CALIFORNIA PROPOSITION 65:**

No chemicals in this material are subject to the reporting requirements.

## **SECTION XVI - OTHER INFORMATION**

 HMIS Health:
 3

 HMIS Flammability:
 0

 HMIS Reactivity:
 0

Coil Kleen O

Additional:

**Specification Information** 

**Department issuing data sheet:** Quality Control

Email address: customerservice@ritekem.com

**Training necessary:** Follow product use instructions listed on the label. Any additional

questions, contact Customer Service at 662-840-6060 or email

customerservice@ritekem.com.

#### Disclaimer:

The information in this Safety Data Sheet and product label is believed to be accurate and reliable as of the date issued. Rite-Kem makes no warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. Accordingly, Rite-Kem will not be responsible for damages resulting from use of or reliance upon this information. The user is responsible for determining whether the Rite-Kem product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application on a Rite-Kem product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Rite-Kem product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.