

Safety Data Sheet

D-Sol

SECTION I - IDENTIFICATION

	Rite-Kem, Inc. 645 Westmoreland Drive Tupelo, MS 38801 (662) 840-6060 Chemtrec :..... (800) 424-9300
---	--

Product Number D-SOL
Product Name D-Sol
Synonyms NSN 7930-01-436-7897
CAS Number 111-76-2
Date Prepared 5/28/2015
Revision Number 4/19/2018
Recommended Use Industrial Use Only

SECTION II - HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Classification

Skin Corrosion/Irritation	Category 3
Serious Eye Damage/Eye Irritation	Category 2B

WARNING!

GHS LABEL:

Hazard Statements

H316	Causes mild skin irritation
H320	Causes eye irritation

Safety Data Sheet

D-Sol

Precautionary Statements

- P264 Wash... thoroughly after handling.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing.
- P332+313 If skin irritation occurs: get medical advice/attention.
- P337+313 If eye irritation persists get medical advice/attention.

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Component Name	CAS #	Component%	OSHA PEL	ACGIH TLV
2-Butoxyethanol	111-76-2		50 ppm	20 ppm

SECTION IV - FIRST AID MEASURES

Contact with eyes: Flush with water for 15 minutes. Seek immediate medical attention.

Skin contact: Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, seek immediate medical attention.

Inhalation: Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is affected or stopped. Seek immediate medical attention.

Ingestion: Induce vomiting.

SECTION V - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, CO2, dry chemical.

Special Fire Fighting Procedures Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

Unusual Fire Fighting Hazards: Vapors may travel considerable distance to a source of ignition where they can ignite, flashback or explode. May create vapor/air explosion hazard indoors, outdoors or in sewers. If container is not properly cooled, it can explode in the heat of a fire.

Safety Data Sheet

D-Sol

SECTION VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep all sources of ignition and hot metal surfaces away from spill or release.

Evacuate all unprotected personnel from the area.

Environmental Precautions: Prevent liquid from entering drains, sewers or waterways.

Contain spill if it can be done with minimal risk.

Notify proper authorities.

Methods for Cleaning Up: Use foam on spills to minimize vapors.

Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container.

SECTION VII - HANDLING AND STORAGE

Handling and Storage:

- Vent container carefully before opening.
- "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
- Keep containers tightly closed when not in use.
- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.
- NFPA Class III A storage.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

Component Name	CAS #	OSHA PEL	ACGIH TLV
2-Butoxyethanol	111-76-2	50 ppm	20 ppm

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

Monitoring:

Follow accepted work practices for handling a flammable material.
Do not eat, drink or smoke in areas where this chemical is used or stored.
Wash hands prior to eating, drinking or using the restroom.
Have eye wash stations and safety showers readily available.

Personal Protective Equipment (PPE)

Eye Protection:

Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

Skin Protection:

Impervious solvent resistant gloves.
Impervious apron and work boots recommend where splashing may occur.

Respiratory Protection:

Safety Data Sheet

D-Sol

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, Yellow Liquid
Odor	Sassafrass Odor
pH@25°C	9.5-10
Melting/Freezing Point	N/E
Flashpoint	N/E
Specific Gravity	1.01
Solubility	Complete
Auto-Ignition Temperature	-
Decomposition Temperature	-
VOC Content	<7%
Odor Threshold	-
Boiling Range	212°F
Evaporation Point	0.1 (Butyl Acetate =1)
Flammable Limits - Upper	N/E
Flammable Limits - Lower	N/E
Vapor Pressure	N/A
Vapor Density (Air=1)	N/A
Viscosity	-

SECTION X - STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: None

Hazardous Decomposition/Byproducts: CO, CO₂, and noxious smoke under extreme fire conditions

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

Incompatibilities: Strong acids and bases, strong oxidizers

Safety Data Sheet

D-Sol

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure: Contact and inhalation; ingestion possible.

Inhalation: May cause irritation to the upper respiratory tract and CNS depression.
Low to moderate degree of toxicity by inhalation.

Eye Contact: Causes eye irritation including stinging, watering and redness which may result in corneal injury.

Skin Contact: Contact may cause mild skin irritation including redness, burning and drying/cracking of the skin.
Repeated or prolonged contact with large amounts of this material may result in absorption through the skin to produce toxic effects.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting and cause chemical pneumonia and edema.
Low degree of toxicity by ingestion.

Toxicity:

Component Name	LD50	LC50
2-Butoxyethanol	Oral - Rat - 470 mg/kg; Dermal - Rabbit - 220 mg/kg;	Inhalation - Rat - 4 h - 450 ppm

Reproductive Effects	Teratogenicity	Mutagenicity	Embryotoxicity	Sensitization to Product	Synergistic Products
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Information not available.

Mobility: Information not available.

Degradability: Information not available.

BioAccumulation: Information not available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow Federal, state, and local regulations.

Safety Data Sheet

D-Sol

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: Non-Hazardous

Contains:

Hazard Class and Label:

Identification Number:

Packaging Group:

Other Shipping Info:

SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

Acute	Chronic	Fire	Pressure	Reactive
X	X	N/A		

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

No chemicals in this material are subject to the reporting requirements.

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

Component Name	CAS #	% by wt.	RQ (lbs.)
2-Butoxyethanol	111-76-2	100%	5,000

CALIFORNIA PROPOSITION 65:

No chemicals in this material are subject to the reporting requirements.

SECTION XVI - OTHER INFORMATION

HMIS Health: 1

HMIS Flammability: 0

HMIS Reactivity: 0

Additional:

Safety Data Sheet

D-Sol

Specification Information

Department issuing data sheet: Quality Control

Email address: customerservice@ritekem.com

Training necessary: Follow product use instructions listed on the label. Any additional questions, contact Customer Service at 662-840-6060 or email customerservice@ritekem.com.

Disclaimer:

The information in this Safety Data Sheet and product label is believed to be accurate and reliable as of the date issued. Rite-Kem makes no warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. Accordingly, Rite-Kem will not be responsible for damages resulting from use of or reliance upon this information. The user is responsible for determining whether the Rite-Kem product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application on a Rite-Kem product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Rite-Kem product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.