Dry Cleaning Solvent

SECTION I - IDENTIFICATION



Rite-Kem, Inc.

645 Westmoreland Drive

Tupelo, MS 38801 (662) 840-6060

Chemtrec :..... (800) 424-9300

Product Number DRY-CLEAN

Product Name Dry Cleaning Solvent

Synonyms NSN 6850-00-274-5421; 6850-00-281-1985; 6850-00-285-8011;

CAS Number Multiple 6850-00-664-5685

 Date Prepared
 5/28/2015

 Revision Number
 4/19/2018

Recommended Use Industrial Use Only

SECTION II - HAZARDOUS IDENTIFICATION

GHS CLASSIFICATION:

Classification

Flammable Liquids

Aspiration Hazard

Category 1

Skin Corrosion/Irritation

Category 2

Serious Eye Damage/Eye Irritation

Category 2B

Specific target organ toxicity, single exposure, N

Category 3

Hazardous to the aquatic environment, acute hazard

Category 3

DANGER!

GHS LABEL:





Hazard Statements

H227 Combustible liquid
 H304 May be fatal if swallowed and enters airways
 H315 Causes skin irritation
 H320 Causes eye irritation
 H336 May cause dizziness or drowsiness
 H402 Harmful to aquatic life

Dry Cleaning Solvent

Precautionary Statements

P501

| P210 | Keep away from heat, hot surfaces, sparks, open flames, and other ignition, sources. No smoking. |
|--------------|---|
| 1 2 10 | Recop untay from float, flot buildeds, sparke, open flames, and build fighted, boardess. No smoking. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P264 | Wash thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated are. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P301+310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| P302+352 | IF ON SKIN: Wash with plenty of water/ |
| P304+340 | IF INHALED: Remove victim to fresh air and keep comfortable for breathing. |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing. |
| P312 | Call a POISON CENTER or a doctor/physician if you feel unwell. |
| P321 | Specific treatment (see on this label). |
| P331 | Do NOT induce vomiting. |
| P332+313 | If skin irritation occurs: get medical advice/attention. |
| P337+313 | If eye irritation persists get medical advice/attention. |
| P362+364 | Take off immediatley all contaminated clothing and wash it before reuse. |
| P370+378 | In case of fire: Use to extinguish. |
| P403 | Store in a well ventilated place. |
| P403+233 | Store in a well ventilated place. Keep container tightly closed. |
| P405 | Store locked up. |

SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

Dispose of contents/container to...

| Component Name | CAS# | Component% | OSHA PEL | ACGIH TLV |
|----------------------------------|------------|------------|-----------------|-----------------|
| Terpene Hydrocarbon | 5989-275 | | Not Established | Not Established |
| Medium Aliphatic Solvent Naphtha | 64742-88-7 | | 100 ppm | 100 ppm |

Dry Cleaning Solvent

SECTION IV - FIRST AID MEASURES

Contact with eyes: Flush with water for 15 minutes. Seek immediate medical attention.

Skin contact: Wash exposed areas with water and mild soap. Remove contaminated clothing

immediatelyand launder before reuse. If irritations persist, seek immediate medical

attention.

Inhalation: Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is

affected or stopped. Seek immediate medical attention.

Ingestion: If swallowed. Do not induce vomiting. Seek immediate medical attetntion.

SECTION V - FIREFIGHTING MEASURES

Suitable Extinguishing Media: Water fog, foam, CO2, dry chemical.

Special Fire Fighting Procedures Use self-contained breathing apparatus and full bunker gear in fire areas.

Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water

used for cooling.

Unusual Fire Fighting Hazards: Product is flammable and may be ignited by heat, sparks, flames or other

sources of ignition (e.g., static electricity, pilot lights or mechanical/electrical equipment). Vapors are heavier than air and may accumulate in low areas. Vapors may travel considerable distancesto a source of ignition where they can ignite, flashback or explode. May create vapor/air explosion hazard indoors, outdoors or in sewers. If container is not properly cooled, it can

explode in the heat of a fire.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Keep all sources of ignition and hot metal surfaces away from spill or

release.

Evacuate all unprotected personnel from the area.

Environmental Precautions: Prevent liquid from entering drains, sewers or waterways.

Contain spill if it can be done with minimal risk.

Notify proper authorities.

Methods for Cleaning Up: Use foam on spills to minimize vapors.

Using only non-sparking tools and explosion proof equipment, collect

spill on absorbent material and put into approved container.

SECTION VII - HANDLING AND STORAGE

Handling and Storage: • Vent container carefully before opening.

 Bond and ground all equipment when transferring from one vessel to another. The use of ecplosion-proof equipment is recommended.

Dry Cleaning Solvent

- "Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources.
- Keep containers tightly closed when not in use.
- Avoid prolonged breathing of mist or vapor. Wash thoroughly after handling.
- NFPA Class III A storage.

SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

EXPOSURE LIMITS:

| Component Name | CAS# | OSHA PEL | ACGIH TLV |
|----------------------------------|------------|-----------------|-----------------|
| Terpene Hydrocarbon | 5989-275 | Not Established | Not Established |
| Medium Aliphatic Solvent Naphtha | 64742-88-7 | 100 ppm | 100 ppm |

Engineering Controls: Adequate local or mechanical to reduce vapor or mist to below the PEL or

TLV.

Monitoring: Follow accepted work practices for handling a flammable material.

Do not eat, drink or smoke in areas where this chemical is uised or stored.

Have eye wash stations and safety showers readily available.

Personal Protective Equipment (PPE)

Eye Protection: Goggles or approved OSHA device with side shields; do not wear contact

lenses when handling this product.

Skin Protection: Impervious solvent resistent gloves.

Impervious apron and work boots recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is

unknownor above the OSHA PEL or ACGIH TLV.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Dry Cleaning Solvent

| | , , |
|---------------------------|-------------------------|
| Appearance | Clear, Colorless Liquid |
| Odor | Mild Odor |
| pH@25°C | - |
| Melting/Freezing Point | N/A |
| Flashpoint | >145 F (TCC) |
| Specific Gravity | 0.79 |
| Soluability | Negligible |
| Auto-Ignition Temperature | - |
| Decomposition Temperature | - |
| VOC Content | 100% (6.6#/gal) |
| Odor Threshold | - |
| Boiling Range | >370°F |
| Evaporation Point | <1 Where Ether=1 |
| Flammable Limits - Upper | 6.0% |
| Flammable Limits - Lower | 1.0% |
| Vapor Pressure | <0.5 mmHg @ 100°F |
| Vapor Density (Air=1) | 6.2 (Air=1) |
| Viscosity | - |
| | |

| SECTION X - : | STABILITY AND | REACTIVITY |
|---------------|---------------|------------|
|---------------|---------------|------------|

Stability: Stable

Conditions to Avoid: Extreme heat and ignition sources.

Hazardous Decomposition/Byproducts: CO and CO2

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

Incompatibilities: Stong oxidizers

Dry Cleaning Solvent

SECTION XI - TOXICOLOGICAL INFORMATION

Likely Route of Exposure: Contact and inhalation; ingestion possible.

Inhalation: May cause irritation to the upper respiratory tract and CNS depression.

Low to moderate degree of toxicity by inhalation.

Eye Contact: Causes eye irritation including stinging, watering and redness which

may result in corneal injury.

Skin Contact: Contact may cause mild sking irritation including redness, burning and

drying/cracking of the skin.

Ingestion: Aspiration hazard. Can enter the lungs during swallowing or vomiting

and cause chemical pneumonia and edema.

Acute Toxicity Value: See Health Hazards below.

Chronic (Long Term) Effects: See Health Hazards above.

Toxicity:

| Component Name | LD50 | LC50 |
|-------------------------------------|-----------------|-----------------|
| Terpene Hydrocarbon | Not Established | Not Established |
| Medium Aliphatic Solvent Naphtha | Not Established | Not Established |

Reproductive Effects Not Applicable

Teratogenicity Not Applicable

Mutagenicity Not Applicable

Embryotoxicity Not Applicable

Sensitization to Product Not Applicable

Synergistic Products Not Applicable

Carcinogenicity Not Listed as a Carcinogen

SECTION XII - ECOLOGICAL INFORMATION

Ecotoxicity: Information not available.

Mobility: Information not available.

Dry Cleaning Solvent

Degradability: Information not available.

BioAccumulation: Information not available.

SECTION XIII - WASTE DISPOSAL CONSIDERATIONS

Follow Federal, state, and local regulations.

SECTION XIV - TRANSPORT INFORMATION

DOT SHIPPING INFORMATION

Proper Shipping Name: Not Regulated

Contains:

Hazard Class and Label: None (Combustible)

Identification Number: Packaging Group: Other Shipping Info:

IMDG: Not Regulated

IATA: Not Regulated

SECTION XV - REGULATORY INFORMATION

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

| Acute | Chronic | Fire | Pressure | Reactive |
|-------|---------|------|----------|----------|
| Χ | X | Χ | | |

SARA TITLE III SECTION 313 SUPPLIER INFORMATION:

No chemicals in this material are subject to the reporting requirements.

CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:

No chemicals in this material are subject to the reporting requirements.

Dry Cleaning Solvent

CALIFORNIA PROPOSITION 65:

No chemicals in this material are subject to the reporting requirements.

SECTION XVI - OTHER INFORMATION

 HMIS Health:
 1

 HMIS Flammability:
 2

 HMIS Reactivity:
 0

Additional:

Specification Information

Department issuing data sheet: Quality Control

Email address: customerservice@ritekem.com

Training necessary: Follow product use instructions listed on the label. Any additional

questions, contact Customer Service at 662-840-6060 or email

customerservice@ritekem.com.

Disclaimer:

The information in this Safety Data Sheet and product label is believed to be accurate and reliable as of the date issued. Rite-Kem makes no warranties, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose or course of performance or usage of trade. Accordingly, Rite-Kem will not be responsible for damages resulting from use of or reliance upon this information. The user is responsible for determining whether the Rite-Kem product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application on a Rite-Kem product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the Rite-Kem product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.